


TOP VIEW


MATERIAL:
HOUSING: PA46,UL94V-0, BLACK.
TERMINAL: PHOSPHOR BRONZE Ø=0.46MM, G/FU" GOLD PLATING.
SHIELD: C2680,T=0.20MM,20 ~50U" MIN NICKEL PLATING
ON ALL AREA.

MACHANICAL:
DURABILITY: 750 CYCLES MIN,12.5MM/MINUTE.
INSERTION FORCE: 2.2KG.F MAX.
RETENTION STRENGTH : 7.7KG.F BETWEEN JACK AND PLUG .
OPERATING TEMPERATURE: -40℃~+85℃.
STORAGE TEMPERATURE: -40℃~+85℃.
ALL CRITICAL DIMENSIONS WITH "*"


ELECTRICAL:
VOLTAGE: 125 VOLTS AC.
CURRENT RATING : 1.5AMP.
DIELECTRIC STRENGTH : 1000 VAC RMS 50HZ OR 60HZ,1 MIN.
INSULATION RESISTANCE: 500 MEGA OHMS MIN. INITIAL
AFTER 500V DC FOR 1 MINUTE.
CONTACT RESISTANCE: SINGLE TERMINAL 30 MILLIOHMS MAX.
INITIAL 50 MILLIOHMS MAX. AFTER
DURABILITY TEST.




LEFT SIDE VIEW




FRONT VIEW




RIGHT SIDE VIEW




BACK VIEW



BOTTOM VIEW





RECOMMENDED PCB LAYOUT
VIEWED FROM COMPONENT SIDE



LED Specification

Standard LED Color	LED Wavelength	Foward(A)	Foward(V)
Green	568nm	20mA	1.6-2.6V
Yellow	585nm	20mA	1.6-2.6V



VOOHU 苏州沃虎电子科技有限公司 Su Zhou Voohu Electronic Tech.Co.Ltd		TITLE: RJ45直通 56带屏蔽带灯	SIZE A4	UNITS MM[INCH]	GENERAL TOLERANCES UNLESS SPECIFIED		APPROVED BY: Geoffrey.Song
		PART NO.: SYT561188DG1A3DY1027	SACLE 1:1	REV A0	$x\pm0.35$	$x^{\circ}\pm3.0^{\circ}$	CHECKED BY:
TEL: +86 400 1048 018		REMARK:	SHEET 1/1		$.x\pm0.30$	$.x^{\circ}\pm2.0^{\circ}$	Elvis.Song
					$.xx\pm0.25$	$.xx^{\circ}\pm1.5^{\circ}$	DESIGND BY:
WEB: WWW.WOHU-TEK.COM					$.xxx\pm0.10$	$.xxx^{\circ}\pm1.0^{\circ}$	Sunny.Xu