


REACH & RoHS
COMPLIANT

1 Features And Benefits


- Very low DC resistance.
- Different turns ratios.
- Small SMD package.
- Operating temperature range -40 °C to 125 °C.
- Switching power supplies.
- Feedback control.
- Overload sensing.
- Load drop/shut down detection.
- RoHS Compliant



2 Electrical Specifications @ 25°C

Part Number	Secondary Inductance (μH)	Current Rating (A)	Turns Ratio	DCR (mΩ)		Hipot (V _{DC})
				Max	Max	
				Primary	Secondary	
				8-7	1-3	
WHPT-EE050-003	80	20	1:20	0.75	400	1000
WHPT-EE050-004	180	20	1:30	0.75	870	1000
WHPT-EE050-005	320	20	1:40	0.75	1140	1000
WHPT-EE050-006	500	20	1:50	0.75	1500	1000
WHPT-EE050-007	720	20	1:60	0.75	1980	1000
WHPT-EE050-008	980	20	1:70	0.75	3000	1000
WHPT-EE050-009	2000	20	1:100	0.75	5500	1000
WHPT-EE050-010	3000	20	1:125	0.75	6500	1000
WHPT-EE050-011	8000	20	1:200	0.75	33240	1000

3 Schematics



● START POIN

VOOHU 苏州沃虎电子科技有限公司
Su Zhou Voohu Electronic Tech.Co.Ltd

TITLE:
SMT Current Sense Transformers

SIZE
A4

UNITS
MM[INCH]

GENERAL TOLERANCES
UNLESS SPECIFIED

APPROVED BY:
Geoffrey.Song

PART NO.:
WHPT-EE050-006

SACLE
1:1

REV
A0

x±0.35
.x±0.30

x°±3.0°
.x°±2.0°


CHECKED BY:
Elvis.Song

TEL: +86 400 1048 018

WEB: WWW.WOHU-TEK.COM

REMARK:
50K---1 MHz Available

SHEET
1/3




.xx±0.25
.xxx±0.10

.xx°±1.5°
.xxx°±1.0°


DESIGND BY:
Sunny.Xu

REACH & RoHS
COMPLIANT


4 Dimensions (mm)& recommend layout




Front view



Side view




Bottom view



Suggested PAD Layout

5 Recommended Reflow Profile



MSL:

Grade: 1 level. Floor life: 0.5 year Condition: $\leq 30^{\circ}\text{C}/60\%\text{RH}$.

Ramp up rate= $3^{\circ}\text{C}/\text{s}$ max Ramp down rate= $6^{\circ}\text{C}/\text{s}$ max

$T_L=217^{\circ}\text{C}$ $t_L=60\text{s}-150\text{s}$ $T_P=250\pm 3^{\circ}\text{C}$ Time within 5°C of actual Peak Temperature (t_P): 20~40s

$T_{s\min}=150^{\circ}\text{C}$ $T_{s\max}=200^{\circ}\text{C}$ $T_{s\min}$ to $T_{s\max}$: 60s-180s, 25°C to peak Temperature: 8minutes max

VOOHU 苏州沃虎电子科技有限公司
Su Zhou Voohu Electronic Tech.Co.Ltd

TITLE:
SMT Current Sense Transformers

SIZE
A4

UNITS
MM[INCH]

GENERAL TOLERANCES
UNLESS SPECIFIED

APPROVED BY:
Geoffrey.Song

PART NO.:
WHPT-EE050-006

SACLE
1:1

REV
A0

$x\pm 0.35$
 $.x\pm 0.30$

$x^{\circ}\pm 3.0^{\circ}$
 $.x^{\circ}\pm 2.0^{\circ}$


CHECKED BY:
Elvis.Song

TEL: +86 400 1048 018

WEB: WWW.WOHU-TEK.COM

REMARK:
50K---1 MHz Available

SHEET
2/3




$.xx\pm 0.25$
 $.xxx\pm 0.10$

$.xx^{\circ}\pm 1.5^{\circ}$
 $.xxx^{\circ}\pm 1.0^{\circ}$


DESIGND BY:
Sunny.Xu

REACH & RoHS
COMPLIANT


6 Packaging specification




Four Reel



Two Inner Carton



Inner Carton



Export Carton

Package Quantity:
One Reel=850 Pcs
One Inner Carton=850*4=3400 Pcs
One Export Carton=3400*2=6800 Pcs

VOOHU 苏州沃虎电子科技有限公司
Su Zhou Voohu Electronic Tech.Co.Ltd

TEL: +86 400 1048 018

WEB: WWW.WOHU-TEK.COM

TITLE:
SMT Current Sense Transformers

PART NO.:
WHPT-EE050-006

REMARK:
50K---1 MHz Available


SIZE
A4

SACLE
1:1

SHEET
3/3

UNITS
MM[INCH]

REV
A0



GENERAL TOLERANCES
UNLESS SPECIFIED

$x \pm 0.35$
 $.x \pm 0.30$
 $.xx \pm 0.25$
 $.xxx \pm 0.10$

$x^\circ \pm 3.0^\circ$
 $.x^\circ \pm 2.0^\circ$
 $.xx^\circ \pm 1.5^\circ$
 $.xxx^\circ \pm 1.0^\circ$

APPROVED BY:
Geoffrey.Song

CHECKED BY:
Elvis.Song

DESIGND BY:
Sunny.Xu