





REACH & RoHS
COMPLIANT



NOTES:
1. ELECTRICAL:
1.1 VOLTAGE RATING: 150 VAC RMS;
1.2 CURRENT RATING: 1.5 AMP @25°C;
1.3 CONTACT RESISTANCE: 20 MILLIOHMS Max.;
1.4 INSULATION RESISTANCE: 1000 MEGOHMS Min. @500 VDC;
1.5 DIELECTRIC STRENGTH: 1000V DC OR AC PEAK;
ONE CONTACT TO ALL OTHER
CONTACTS CONNECTED TOGETHER
@0.5mA 50Hz or 60Hz a minute.

2. MECHANICAL:
2.1 HOUSING: SEE TABLE;
2.2 TERMINALS: Ø0.46mm PHOSPHOR BRONZE
2.3 PLATING: GOLD FLASH OVER NICKEL 50u" Min.
2.4 DURABILITY: 750 TIMES.
2.5 MATING/UNMATING FORCE: 20N Max.
2.6 RETENTION STRENGTH: 50N FOR 60S±5S.

3. ENVIRONMENTAL:
3.1 STORAGE TEMPERATURE :
-40°C~+85°C RELATIVE HUMIDITY<80%
3.2 OPERATION TEMPERATURE: -40°C~+85°C
3.3 GUARANTEE PERIOD :12 MONTHS
3.4 WAVE-SOLDERING
MATES WITH MODULAR PLUG CONFORMING
TO FCC PART 68, SUBPART F.

1. 电气特性:
1.1. 额定电压: 150 VAC RMS
1.2. 额定电流: 1.5 AMPS@25°C
1.3. 接触电阻: 20mΩ Max.
1.4. 绝缘电阻: 1000 MΩ Min.@500 VDC
1.5. 耐压强度: 端子之间: 1000V DC OR AC 峰值
端子与屏蔽壳之间: 1500V DC OR AC 峰值
@0.5mA 50Hz 或 60Hz 一分钟.

2. 机械特性:
2.1 胶壳: 见表格
2.2 金针: Ø0.46 磷青铜;
2.3 金针电镀: 镀金见料号表格, 镀底50u";
2.4 信赖性: 750次
2.5 插入力/拔出力: 20N Max.
2.6 配合强度: 50N FOR 60S±5S.

3. 环境特性:
3.1. 储存温度: -40°C~+85°C 相对湿度<80%.
3.2. 工作温度: -40°C~+85°C
3.3. 储存时间: 12个月
3.4. 波峰焊.

TITLE:
RJ45直通 56带屏蔽带灯
PART NO.:
SYT561188DB1A3DY1027

SIZE
A4
SACLE
1:1
REV
A0

UNITS
MM[INCH]
GENERAL TOLERANCES
UNLESS SPECIFIED
x±0.35
x°±3.0°
.x±0.30
.x°±2.0°
.xx±0.25
.xx°±1.5°
.xxx±0.10
.xxx°±1.0°

APPROVED BY:
Geoffrey.Song
CHECKED BY:
Elvis.Song
DESIGN BY:
Sunny.Xu

REMARK:

SHEET
1/1



VOOHU 苏州沃虎电子科技有限公司
Su Zhou Voohu Electronic Tech.Co.Ltd

TEL: +86 400 1048 018

WEB: WWW.WOHU-TEK.COM